



# Thermia iTec



iTec

**The air source heat pump that delivers maximum performance and comfort, year round.**

**Thermia iTec** is an air source heat pump with inverter technology. The inverter-controlled compressor adjusts the heat load constantly according to the current heat demand. You never use more energy than is needed, and this of course reduces your energy bills further.

Energy is collected from the outdoor air, and is used to heating of hot water and hydronic heating systems, delivering efficient energy savings at temperatures as low as  $-25^{\circ}\text{C}$ . By a unique acoustic design, it is very quiet in operation. The cooling function assures a pleasant indoor climate also during the hottest period of the year. And if you have a swimming pool, you can reduce the heating cost significantly as Thermia iTec is prepared for heating of pools. With a high seasonal performance Thermia iTec allows you to reduce your energy consumption by up to 75%.

Thermia iTec is available in three output sizes: 5 kW, 9 kW and 16 kW. It consists of two parts: the heat pump itself, which is installed outdoors, and an indoor unit. You can choose from four versions of the indoor unit, each with different features. The choice of unit depends on the set-up of your heating system, to ensure you never pay for more than you actually need. With Thermia Online you have the ability to remotely control and monitor your heat pump.



A+++ energy class when the heat pump is part of an integrated system  
A+++ energy class when the heat pump is the sole heat generator  
Energy class according to Eco-design Directive 811/2013



# Technical data iTec

## Connection

- 1 Supply line heating system: R25, steel, external thread (rear side of the heat pump)
- 2 Return line heating system: R25, steel, external thread (rear side of the heat pump)
- 3 Power and communication wiring conduits (iTec 5 right upper side of the heat pump, iTec 9 and iTec 16 bottom right side of the heat pump)

## Indoor unit



W: 380 mm  
D: 204 mm  
H: 600 mm



W: 420 mm  
D: 260 mm  
H: 730 mm + 50 mm pipe



W: 596 mm  
D: 690 mm  
H: 1845 mm



W: 596 mm  
D: 690 mm  
H: 1538 mm

### ▶ STANDARD

- Intelligent Controller

### ▶ PLUS


- Intelligent Controller
- Immersion heater (3/6/9/12/15 kW 3~400V; 3/6/9 kW 1~230 V)
- Optimum controlled circulation pump Class A
- Three way valve for heating or hot water production

### ▶ TOTAL ▶ TOTAL +60

- Intelligent Controller
- Hot water tank, 180 litre
- Optimum controlled circulation pump Class A
- Three way valve for heating or hot water production
- Immersion heater (3/6/9/12/15 kW 3~400 V; 1,5/3/4,5 kW 1~230 V)
- Total +60 feature extra 60 liters volume tank and 12 liters expansion vessel.


### ▶ TOTAL ▶ TOTAL COMPACT

## Outdoor unit



### ▶ iTec 5

1,67 – 5 kW  
1~230 V



### ▶ iTec 9

2,20 – 9 kW  
1~230 V  
3~400 V



### ▶ iTec 16

3,75 – 16 kW  
1~230 V  
3~400 V

iTec	1~230 V, 50 Hz						3~400 V, 50 Hz	
	5		9		16		9	16
<b>Refrigerant</b>	Type	R410A		R410A		R410A		R410A
	Amount <sup>10</sup>	1.15		1.4		2.6		1.5
	Test pressure	12.3		12.3		12.3		12.3
	Design pressure	4.1		4.1		4.1		4.1
<b>Compressor</b>	Type	BLDC Twin Rotary POE		BLDC Twin Rotary POE		BLDC Twin Rotary PVE		BLDC Twin Rotary PVE
	Oil							
<b>Electrical data</b>	Main supply	230		230		230		400
	Rated power, cooling	1,21		1,95		3,84		1,92
	Rated power, heating	1,67		2,20		3,75		2,20
	Fuse	16		16		32		10
<b>Performance</b>	COP <sup>1</sup>	4.72		4.21		4.21		4.21
	Heating capacity <sup>1</sup>	5.0		9.0		16.0		9.0
	Power input – heating <sup>1</sup>	1.06		2.14		3.8		2.14
	EER <sup>2</sup>	4.13		3.85		3.65		3.65
	Cooling capacity <sup>2</sup>	5.0		7.5		14.0		7.0
	Power input – cooling <sup>2</sup>	1.21		1.95		3.84		1.92
	SCOP 14825 (Average climate) Low temp	4.56		4.39		4.41		4.47
	SCOP 14825 (Cold climate) Low temp	3.78		3.99		3.90		3.97
	SCOP 14825 (Average climate) High temp	3.19		3.19		2.82		3.26
	SCOP 14825 (Cold climate) High temp	2.54		2.88		2.74		2.73
<b>Energy class - system</b> <sup>8</sup>	Floor heating (35°C)/Radiator (55°C)	A+++ / A++		A+++ / A++		A+++ / A++		A+++ / A++
<b>Energy class - product</b> <sup>9</sup>	Floor heating (35°C)/Radiator (55°C) Domestic hot water	A+++ / A++ A		A+++ / A++ A		A+++ / A++ A		A+++ / A++ A
<b>Nominal flow</b> <sup>3</sup>	Heating circuit	0.24		0.43		0.76		0.36
<b>Operating range</b> (outdoor)	Heating	-25~+35		-25~+35		-25~+35		-25~+35
	Cooling	+10~+46		+10~+46		+10~+46		+10~+46
	Domestic hot water	-25~+43		-25~+43		-25~+43		-25~+43
<b>Max temperature</b> <sup>4</sup>	Heating circuit	55		55		55		55
<b>Sound power level</b>	Regular mode <sup>5</sup>	61		63		66		63
<b>Sound pressure level</b>	1m <sup>6</sup>	46		48		51		48
	4m <sup>7</sup>	44		46		49		46
<b>Weight</b>	Outdoor unit	59		76		108		76
	Standard	18		18		18		18
	Plus	21		21		21		21
	Total	106		106		106		106
	Total +60	142		142		142		142
	Total Compact	100		100		100		100
<b>Dimensions (WxDxH)</b>	Outdoor unit	880 x 310 x 798		940 x 330 x 998		940 x 330 x 1420		940 x 330 x 998

The measurements are performed on a limited number of heat pumps which can cause variations in the results. Tolerances in the measuring methods can also cause variations.

- 1) At A7/W35 according to EN 14511.
- 2) At A35/W7 according to EN 14511.
- 3) Nominal flow: heating circuit 10K.

4) At minimum outdoor temperature 0°C.

5) According to EN 12102, nominal operation A7W35

6) According to EN 11203, nominal operation A7W35, heat pump ground mounted against building facade

7) Quarter spherical sound propagation in free field, nominal operation A7W35, heat pump ground mounted against building facade

8) When the heat pump is part of an integrated system. According to Eco-design Directive 811/2013

9) When the heat pump is the sole heat generator and the built-in controller is not included.

According to Eco-design Directive 811/2013.

10) The refrigerant circuit is hermetically sealed and subject to the F-gas directive. Global Warming Potential (GWP) for R410A according to EC 517/2014 is 2088, giving a CO<sub>2</sub> equivalent corresponding to 5kw SP: 2401 kg, 9 kw SP: 2923 kg, 9 kW: 3132 kg, 16 kw SP: 5429 kg, 16 kW: 5429 kg

Thermia Heat Pumps reserves the right to make changes without further notice.